

Wheels

Job No.

40-0

A. Disk Wheels

All cars of Models 180 to 220 SE are fitted with 13" steel disk wheels. With the exception of Model 190 SL all export models can be fitted with 15" disk wheels as an optional extra.

The disk wheels of Models 180, 180 a, 180 D, 190 D, 190 SL, 220 a, 219, 220 S, and 220 SE are provided with rim balancing slots for balancing the wheels, whereas the disk wheels on Models 180 b, 180 Db, 190 b, and 190 Db have no rim slots (see Job No. 40-2).

Disk Wheels

Model	180 180 a 180 D 190 D	180 b, 180 Db 190, 190 b 190 Db	190 SL	219	220 a 220 S 220 SE
Standard version					
Rim type	Well base rim				
Rim designation	4½ Kx 13—A	4½ Kx 13—B	5 Kx 13—B	5 Kx 13—B	5 Kx 13—B
Rim version	symmetrical	asymmetrical			
Optional version					
Rim type	Well base rim				
Rim designation	4½ Kx 15—A	—		4½ Kx 15—A	
Rim version	symmetrical	—		symmetrical	
Test Values of Disk Wheels					
Permissible eccentricity	1.5 mm		1.0 mm	1.5 mm	
Permissible run-out	1.5 mm				
Permissible unbalance	750 cmg				