

Table 20

## REAR AXLE

Group 35

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
		<u>REAR AXLE TUBE</u>		
45	180 350 44 19	Rear axle tube, left, with thrust arm support and locking screw	1	
46	180 350 32 19	Rear axle tube, right, with thrust arm support	1	
47	180 351 01 50	Bushing (for rear axle tube, right)	2	
48	-	Locking screw M 24x1,5 DIN 906 (for oil filling at rear axle tube, left)	1	only valid for rear axle tube 180 350 44 19
49	180 350 02 90	Fan (for rear axle tube)	1	
		<u>SLIDING JOINT</u>		
53	180 350 05 13	Sliding joint, supported by roller bearing	1	
54	180 357 00 52	Washer	2	) in joint ) fork
55	-	Circlip 48x1, 75 DIN 472	2	
56	180 357 00 13	Universal spider	1	
57	120 357 01 14	Needle bearing bushing	4	
58	-	Needles 2,5 Ø x 11,8 DIN 617	100	
59	120 994 01 35	Snap ring 2, 25 mm thick	a.r.)	) optional
-	120 994 04 35	Snap ring 2, 35 mm thick	a.r.)	
-	120 994 06 35	Snap ring 2, 40 mm thick	a.r.)	

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
-	120 994 07 35	Snap ring 2, 45 mm thick	a.r.)	) optional
-	120 994 08 35	Snap ring 2, 55 mm thick	a.r.)	
60	180 350 07 13	Sliding sleeve with guide plate	1	
61	-	Circlip 32x1, 5 DIN 471	2	
62	180 981 00 86	Cylindr. roller 4 x 4	132	
63	180 357 05 91	Rubber sleeve	1	
64	180 353 00 76	Tightening screw, interior	1	) for joint fork
65	-	Lock washer B 10 DIN 127	1	
66	180 353 30 52	Shim 1.00 mm thick )	1	) for joint fork, interior
		)		
-	180 353 31 52	Shim 1.10 mm thick )	1	
		)		
-	180 353 33 52	Shim 1.20 mm thick )	1	
		)		
-	180 353 35 52	Shim 1.30 mm thick )	1	
		)		
-	180 353 37 52	Shim 1.40 mm thick )	1	
		) optional		
-	180 353 39 52	Shim 1.50 mm thick )	1	
		)		
-	180 353 41 52	Shim 1.60 mm thick )	1	
		)		
-	180 353 43 52	Shim 1.70 mm thick )	1	
		)		
-	180 353 45 52	Shim 1.80 mm thick )	1	
		)		
-	180 353 47 52	Shim 1.90 mm thick )	1	
		)		
-	180 353 49 52	Shim 2.00 mm thick )	1	