



Table 18

## FRONT AXLE

Group 33

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
		<u>FRONT AXLE</u>		
1	121 330 02 42	Front axle support with rear engine mounting	1	
2	121 460 02 35	Bracket (for steering shock absorber, welded on)	1	
3	181 333 01 65	Rubber buffer	2	
4	121 330 02 98	Front axle half, left	1	
5	121 330 03 98	Front axle half, right	1	
6	180 330 22 20	Steering knuckle, left (without locking groove with right- hand thread)	1	
7	180 330 23 20	Steering knuckle, right (without locking groove with right- hand thread)	1	
8	180 332 01 48	Bushing 38 mm long	4	
9	-	Cylindr. pin 2, 5 h8x6 DIN 7	2	
10	-	Grease fitting B 8 DIN 71412	2	
11	120 332 02 60	Dust cover	4	
12	120 332 00 51	Dust sleeve	2	
13	120 332 05 06	King pin	2	
14	-	Grease fitting B 8 DIN 71412	2	

Table 18

## FRONT AXLE

Group 33

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
15	120 332 01 62	Pressure plate, bottom	2	
16	120 332 02 62	Pressure plate, top	2	
17	136 332 00 52	Shim 2.30 mm thick )	2	)
		)		)
-	136 332 01 52	Shim 2.50 mm thick )	2	)
		)		)for king pin
-	136 332 02 52	Shim 2.70 mm thick )	2	)at steering
		) optional		)knuckle,
-	136 332 08 52	Shim 1.70 mm thick )	2	)bottom
		)		)
-	136 332 09 52	Shim 1.90 mm thick )	2	)
		)		)
-	136 332 10 52	Shim 2.10 mm thick )	2	)
18	120 333 05 09	Steering knuckle support	2	
19	-	Grease fitting A 8 DIN 71412	2	
20	181 994 00 15	Locking plate	2	
21	-	Hex. nut M 14 x 1, 5 DIN 934-5 S	2	
		<u>FRONT WHEEL HUB</u>		
22	180 330 07 25	Front wheel hub with pin	2	
23	120 401 01 71	Wheel fixing pin	10	
24	-	Tapered roller bearing 32206 DIN 720	2	
25	180 334 01 64	Puller ring )	2	) for front wheel hub
26	000 997 18 46	Sealing ring )	2	)