

Technical Specifications

Job. No.

00-1

Change: Models 180 c and 180 Dc added, changes at *)

I. Models 180, 180a, 180b, 180c and 190 SL

Models

Car model	180	180a	180b	180c	190 SL
Chassis type	120.01	120.01	120.01	120.01	121.04
Engine model	M 136.VII	M 121 B.IV	M 121 B.IV-b	M 121 B.VIII	M 121 B.II ²⁾ M 121 B.IX ³⁾ *
Engine type	136.925	121.923	121.923	121.927	121.921 ²⁾ 121.928 ³⁾ *

Engine

Operation	4-cycle carburetor			
No. of cylinders	4			
Bore/Stroke (mm)	75/100	85/83.6		
Total eff. piston displacement (cm³)	1767	1897		
Compression ratio ϵ	6.7:1	6.8:1	7.0:1	8.8:1 ⁴⁾
Firing order	1-3-4-2			
Max. speed (rpm)	4500	6000		
Engine performance in metric HP at rpm acc. to DIN ¹⁾ in gr. HP/rpm acc. to SAE	52/4000 58/4000	65/4500 74/4700	68/4400 78/4500	105/5700 120/5800
Max. torque mkg/rpm acc. to DIN mkg/rpm acc. to SAE	11.4/1800 11.7/1800	13.0/2200 14.4/2800	13.2/2500 14.8/2500	14.5/3200 15.8/3800
Crankshaft bearings	3 Babbit metal plain bearings with steel-backed shells	3 compound plain bearings with steel-backed shells		
Connecting rod bearings	compound plain bearings with steel-backed shells			
Valve arrangement	side	overhead		
Camshaft location	lateral	overhead		
Oil cooling	—	Oil-water heat exchanger		
Cooling system	Water circulation through pump, thermostat with by-pass pipe and fan			
Lubrication	Forced-feed lubrication by means of gear-type pump			

¹⁾ The HP output stated is actually available for the car at the clutch, since the power used by the engine accessories has already been deducted.

²⁾ Up to use of further developed valve controls.

³⁾ As from use of further developed valve controls.

⁴⁾ Up to engine No. 6503803 compression ratio $\epsilon = 8.5 : 1$.

Model	180	180 a	180 b	180 c	190 SL
-------	-----	-------	-------	-------	--------

Electric Equipment

Battery	Voltage (V) Capacity (Ah)	6 84	12 56	12 52	12 56
---------	------------------------------	---------	----------	----------	----------

Dimensions

Wheel track (mm) front rear	1420 1460 ¹⁾	1440 ²⁾ 1485 ²⁾	1440 1485	1440 ²⁾ 1485 ²⁾ ³⁾
Wheel lock, inner outer	39° 30°			
Min. turning circle (m)	approx. 11		approx. 10.7	
Wheel base (mm)	2650			2400
Length of vehicle (mm)	4460	4485	4500	4290
Width of vehicle (mm)	1740			1760
Height of vehicle, ready for driving (mm)	approx. 1560			app. 1320
Ground clearance, vehicle with 2 persons (mm)	approx. 195			app. 155

Weights

Dry weight of vehicle without fuel, spare wheel and tools (kg)	1070	1085	1075 ⁴⁾
Unladen weight of vehicle, ready for driving, with full fuel tank, spare wheel and tools (kg)	1150	1165	1160 ⁵⁾
Perm. total weight (kg)	1160	1615	1440
Perm. axle load (kg) front/rear	720/880	735/880	690/750

Capacities

Cool. system with heating (ltr.) Water	9	10
Fuel tank / fuel reserve (ltr.) Fuel	56/5	65/6
Crankcase (ltr.) Engine oil max./min.	4/2.5	
Oil filter (ltr.) Engine oil	0.5	
Water pump (cm³) Hypoid oil SAE 90	10	
Transmission (ltr.) Automatic Transmission Fluid	1.4	
Rear axle (ltr.) Hypoid oil SAE 90	2.25 ⁶⁾	
Steering (ltr.) Hypoid oil SAE 90	0.3	
Brake system (ltr.) ATE blue brake fluid	0.5	
Wheel hub front g) Anti-friction bearing grease	65	

¹⁾ On model 180 with twin-jointed rear axle 1450 mm.

²⁾ For rim size 5 JK × 13-B (2nd type); for rim size 4 1/2 K × 13-B (1st type) wheel track front 1430, rear 1475.

³⁾ Previously 1470 mm.

⁴⁾ Applies to roadster, for coupe 1095 kg.

⁵⁾ Applies to roadster, for coupe 1180 kg.

⁶⁾ On model 180 with 2-jointed rear axle 1.6 ltr.

Model	180	180 a	180 b	180 c	190 SL
-------	-----	-------	-------	-------	--------

Speeds, Consumption Figures and Operating Conditions

At rear axle ratio of i =	1:3.89	1:3.90		1:3.90 ⁴⁾
Max. speed for individual gears (km/h)				
timed 1st gear	34	42		50
2nd gear	58	74		76
3rd gear	90	117		120
4th gear	approx.126	approx. 135		approx.175
Climbing ability (%)				
1st gear	43	54		50
2nd gear	23	27.5		30
3rd gear	13	15.5		17
4th gear	8	8.8		9.5
Acceleration time in 4th gear from 20–100 km/h ¹⁾ (sec)	38	33	32	25 ²⁾
Engine speed at 100 km/h in 4th gear (rpm)	3390	3370	3350	3380
Fuel consumption for average high-way travel (ltr./100 km)	—	8–12	7.5–11.5	8.2–12.3
Fuel consumption acc. to DIN 70030 ³⁾ (ltr./100 km)	⁴⁾	10.9 at 101 km/h		10.9 at 110 km/h
Engine oil consumption (ltr./100 km)	0.15			
Cool. Water working temperature (° C)	70–95			
Fuel	regular fuel			premium ⁷⁾ (super)
Anti-Knock rating (Octane rating min. ROZ)	82	86		96
for optimal efficiency ³⁾ with max. retardation of ignition and corresponding drop in output	80			90

¹⁾ Vehicle with 2 persons.

²⁾ Measured at $\frac{3}{4}$ of max. speed 110 km/h + 10 %.

³⁾ Gasoline engines are set for optimal output in the factory using commercial fuels. If exceptional cases for a short period demand the use of fuels having an octane rating below that stated for optimum output, ignition should in all cases be retarded correspondingly.

⁴⁾ For gear ratio 2nd type; for gear ratio 1st type und rear axle ratio i = 1 : 3.89/3.90 i = 1 : 3.70
Max. speed 52/89/140/approx. 175 54/93/148/approx. 175
Hill climbing ability 48/26/15/9.0 45/23/13/8.5

⁵⁾ Acceleration period in 4th gear from 30 to 100 km/h in sec.

⁶⁾ Standard fuel consumption 8.7 ltr./100 km; measured at $\frac{2}{3}$ of max. speed, 80 km/h + 10 %.

⁷⁾ Gasoline-benzene mixture, respectively.

II. Models 180 D, 180 Db, 180 Dc, 190 D and 190 Db

Models

Car Model	180 D	180 Db	180 Dc	190 D	190 Db
Chassis Type	120.11	120.11	120.11	121.11	121.11
Engine Model	OM 636.VII	OM 636.VII	OM 621.IV	OM 621.I	OM 621.I
Engine Type	636.930	636.930	621.914	621.910	621.910

Engine

Operation	4-cycle diesel Daimler-Benz constant flow principle precombustion chamber		
Number of cylinders	4		
Bore/Stroke (mm)	75/100	87/83.6	85/83.6
Total effective piston displacement (cm ³)	1767	1988	1897
Compression ratio ϵ	19:1	21 : 1	
Injection order	1-3-4-2		
Max. speed (rpm)	3600	3800	4000
Engine performance in metric HP at rpm acc. to DIN ¹⁾ in gr. HP at rpm acc. to SAE	43/3500 46/3500	48/3800 52.4/3800	50/4000 55/4000
Torque max. in mkg/rpm acc. to DIN in mkg/rpm acc. to SAE	10.3/2000 10.6/2000	11/2200 11.4/2200	11/2200 11.5/2200
Crankshaft bearings	3 compound plain bearings with steel-backed shells		
Connecting rod bearings	compound plain bearings with steel-backed shells		
Valve arrangement	overhead		
Camshaft location	lateral	overhead	
Oil cooling	—	Oil-water heat exchanger	
Cooling system	Water circulation by means of pump, thermostat with by-pass pipe, fan		
Lubrication	Forced-feed lubrication by means of gear-type pump		

¹⁾ The metric horsepower specified is actually available at the clutch, since the power used by the engine accessories has already been deducted.

Model	180 D	180 Db	180 Dc	190 D	190 Db
-------	-------	--------	--------	-------	--------

Electrical Equipment

Battery	Voltage (V) Capacity (Ah)	12 84	12 66	12 84
---------	------------------------------	----------	----------	----------

Dimensions

Wheel track (mm) front rear	1420 1460 ¹⁾	1430 1475	1440 1485	1420 1460	1430 1475
Wheel lock inner outer	39° 30°				
Min. turning circle (m)	approx. 11	approx. 10.7			
Wheel base (mm)	2650				
Length of vehicle (mm)	4485	4500		4485	4500
Width of vehicle (mm)	1740				
Height of vehicle, ready for driving (mm)	approx. 1560				
Ground clearance, carrying 2 persons (mm)	approx. 195				

Weights

Dry weight of vehicle (kg) without fuel, spare wheel and tools	1130	1140
Unladen weight of vehicle, ready for driving, with full fuel tank, spare wheel, tools (kg)	1210	
Perm. total weight (kg)	1650	1660
Perm. axle load (kg) front/rear	770/880	780/880

Capacities

Cool. System with heating (ltr.) Water	8	10.3
Fuel tank / fuel reserve (ltr.) Fuel	56/5	
Crankcase (ltr.) Engine oil max./min.	4/2.5	
Oil filter (ltr.) Engine oil	0.5	
Water pump (cm³) Hypoid oil SAE 90	10	
Transmission (ltr.) Autom. Transm. Fluid	1.4	
Rear axle (ltr.) Hypoid oil SAE 90	2.25 ²⁾	
Steering (ltr.) Hypoid oil SEA 90	0.3	
Brake system (ltr.) ATE blue brake fluid	0.5	
Wheel hub front (g) anti-friction bearing grease	65 each	

¹⁾ For vehicles with twin-jointed rear axle 1450 mm.

²⁾ On Model 180 D with twin-jointed rear axle 1.6 ltr.

Model	180 D	180 Db	180 Dc	190 D	190 Db
-------	-------	--------	--------	-------	--------

Speeds, Consumption Figures and Operating Conditions

At rear axle ratio of $i =$	1:3.70	1:3.90	1:3.70
Max. speed in the individual gears (km/h)			
timed 1st gear	28		30
2nd gear	48		53
3rd gear	75		84
4th gear	approx. 110 ³⁾		approx. 120 ⁴⁾
Climbing ability (%)			
1st gear	35	38	36
2nd gear	19	20	19
3rd gear	11	12	11
4th gear	6	6.5	6
Acceleration time in 4th gear from 40–100 km/h ¹⁾ (sec)	39	36	32
Engine speed at 100 km/h in 4 th gear (rpm)	3220	3350	3220
Fuel consumption for average high-way travel (ltr./100 km)	5.7–7.8	6.0–8.0	5.7–8.0
Fuel consumption acc. to DIN 70030 ²⁾ (ltr./100 km)	6.8 at 82.5 km/h	7.1 at 82.5 km/h	7.1 at 90 km/h
Engine oil consumption (ltr./100 km)	0.15		
Cooling water working temperature (° C)	70–95		
Fuel	Diesel fuel acc. to DIN 51601		

¹⁾ Vehicle carrying 2 persons.

²⁾ Determined at $\frac{3}{4}$ of max. speed 110 km/h + 10 %.

³⁾ For Model 180 Dc a max. speed of 117 km/h must on no account be exceeded on down grades.

⁴⁾ On down grades a max. speed of 130 km/h must on no account be exceeded.

III. Models 220 a, 219, 220 S, and 220 SE

Car model	220 a	219	220 S	220 SE		
Chassis type	180.01	105.01	180.01 ²⁾	128.01 ³⁾		
Engine model	M 180.II	M 180.II	M 180.III	M 127.I		
Engine model	180.921	180.921	180.924	127.980		
A. Engine						
Operation	Four-cycle carburetor			Four-cycle gasoline injection		
Number of cylinders	6					
Bore/stroke (mm)	80:72.8					
Total effective piston displacement (cc)	2195					
Compression ratio ϵ	7.6:1	7.6:1	8.7:1	7.6:1	8.7:1	8.7:1
Firing or injection order	1—5—3—6—2—4					
Maximum R.P.M.	6000					
Engine performance in metric HP at R.P.M. according to DIN ¹⁾ in gr HP at R.P.M. according to SAE	85/4800 92/4800	85/4800 92/4800	90/4800 100/5000	100/4800 112/5000	106/5000 120/5200	115/4800 130/5000
Maximum torque in mkg at R.P.M., DIN rating in mkg at R.P.M., SAE rating	16.0/2400 16.5/2500	16.0/2400 16.5/2500	17.0/2400 18.0/2700	16.3/3500 17.8/3800	17.5/3500 19.0/3600	19.0/3800 20.2/3800
Crankshaft bearings	4 Compound plain bearings with steel-backed shells					
Connecting rod bearings	Compound plain bearings with steel-backed shells					
Valve arrangement	Overhead					
Camshaft location	Top					
Oil cooling	Oil-water heat exchanger					
Cooling system	Water circulation through pump, thermostat with by-pass pipe and fan					
Lubrication	Force-feed lubrication by means of gear-type pump					

¹⁾ The metric horsepower specified is actually available at the clutch, since the power used by the engine accessories has already been deducted.

²⁾ Chassis type for Convertible A 180.030 and Coupé A 180.037.

³⁾ Chassis type for Convertible A 128.030 and Coupé A 128.037.

Model		220 a	219	220 S	220 SE
B. Electrical Equipment					
Battery	voltage (V) capacity (Ah)	12 56			
C. Dimensions					
Track (mm)	front rear	1430 1470			
Wheel lock	inner outer	39° 30°	39° 35°		
Minimum turning circle (m)		appr. 11			
Wheel base (mm)		2820	2750	Sedan 2820	Convertible and Coupé 2700
Length of vehicle (mm)		4715	4680	4750	4700
Width of vehicle (mm)		1740		1740	1790
Height of vehicle curb condition (mm)		appr. 1560		appr. 1560	appr. 1530
Ground clearance carrying 2 persons (mm)		appr. 215	appr. 205	appr. 215	
D. Weights					
Dry weight of vehicle (kg) without fuel, spare wheel and tools		1180	mech. clutch 1170 autom. clutch 1185	Sed. 1230 Conv. 1290 Coupé 1255 1245 1305 1270	Sed. 1250 Conv. 1310 Coupé 1275 1265 1325 1290
Unladen weight of vehicle, with full fuel tank, spare wheel and tools (kg)		1280	mech. clutch 1260 autom. clutch 1275	1325 1385 1350 1340 1400 1365	1345 1405 1370 1360 1420 1385
Load capacity (kg)		450	mech. clutch 465 autom. clutch 450	465 405 440 450 390 425	465 405 440 450 390 425
Permissible total weight (kg)		1730	1725	1790	1810
Permissible axle load (kg) front		810	825	840	860
rear		920	900	950	950
E. Capacities					
Cooling system with heating (ltr)		11.3			
Fuel tank / fuel reserve (ltr)		64/5.5	56/5	64/5.5	60/5.5
Crankcase (ltr) Engine oil max./min.		6/3.5			
Oil filter (ltr) Engine oil		0.5			
Water pump (cc) Hypoid oil SAE 90		10			
Transmission (ltr) Automatic transmission fluid		1.4			
Rear axle (ltr) Hypoid oil SAE 90		2.25			
Steering (ltr) Hypoid oil SAE 90		0.3			
Brake system (ltr) ATE blue brake fluid		0.5			
Wheel hub front (g) Anti-friction bearing grease		65 each			

Model	220 a	219	220 S	220 SE
F. Speeds, Consumption Figures, and Operating Conditions				
At rear axle ratio i =	1:4.11/4.10	1:4.10 1:3.90	1:4.10	1:4.10
Maximum speeds in the individual gears (km/h) timed				
1st gear	44	40 42	49	49
2nd gear	68	69 74	76	76
3rd gear	110	110 117	119	119
4th gear	appr. 150	appr. 148 appr. 184	appr. 160	appr. 160
Climbing ability (%)				
1st gear	52	52 55	$\epsilon=7.6:1$ $\epsilon=8.7:1$ 52 55	60
2nd gear	30	30 31.5	30 31.5	34
3rd gear	18	18 18.5	18 18.5	19
4th gear	10	10.5 10.6	10.5 10.6	10.7
Acceleration time in 4th gear from 20 to 100 km/h (sec.)	27	$\epsilon=7.6:1$ $\epsilon=8.7:1$ 27 26	$\epsilon=7.6:1$ $\epsilon=8.7:1$ 27 25	23
Engine speed at 100 km/h in 4th gear (rpm)	3470	3580 3370	3470	3470
Fuel consumption Fuel consumption for average highway travel (ltr/100 km)	—	$\epsilon=8.7:1$ mech. cl. 9.0—12.5 aut. cl. 9.3—13.0	$\epsilon=8.7:1$ 9.0—12.0 9.3—12.5	8.7—12 9.0—12
Fuel consumption according to DIN 70030 ¹⁾ (ltr/100 km)	—	$\epsilon=8.7:1$ mech. cl. 11.2 at 110 km/h aut. cl. 11.4 at 110 km/h	$\epsilon=8.7:1$ mech. cl. 10.7 at 110 km/h aut. cl. 10.9 at 110 km/h	mech. cl. 10.7 at 110 km/h aut. cl. 10.9 at 110 km/h
Rated fuel consumption ²⁾ (ltr/100 km)	9.8	$\epsilon=7.6:1$ 9.8	$\epsilon=7.6:1$ 9.6	—
Engine oil consumption (ltr./100 km)	0.15			
Cooling water working temperature (°C)	70—95			
Fuel	Premium or benzol-gasoline fuel			
Anti-knock rating (octane rating ROZ) ³⁾	—	$\epsilon=7.6:1$ $\epsilon=8.7:1$ — 96—99	$\epsilon=7.6:1$ $\epsilon=8.7:1$ — 96—99	— 96—99
Minimum anti-knock rating ROZ ⁴⁾	87	87 90	87 90	93

1) Determined at $\frac{3}{4}$ of the maximum speed, at a maximum of 110 km/h with a 10 % increase.

2) Determined at $\frac{2}{3}$ of the maximum speed, at a maximum of 80 km/h with a 10 % increase.

3) The gasoline engines are adjusted at our works with commercial fuels of the anti-knock rating given above (measured in accordance with the research method, ROZ). When fuels of a lower octane rating are used the ignition must be adjusted accordingly.

4) In Models 219 and 220 S with a compression ratio of $\epsilon = 6.8:1$ (optional extra, see Job-No. 01-3/3, Section B) the minimum octane rating ROZ is 80.