

Rear Engine Suspension

Job No.

24-0

A. Three-Point Engine Suspension on Models 180, 180 a, 180 b, 180 D, 180 Db, 190 D, 190 Db, 190 SL, 220 a, and 219

Rear rubber mountings

Model	Part No. of rubber mounting	Shore hardness of rubber
180, 180 a, 180 b, 180 Db, 190 Db, and 190 SL 1 st version ¹⁾	120 240 04 18	40°—50°
220 a, 219	180 240 03 18 as replacement part 180 240 05 18	

¹⁾ Cars of Model 190 SL are equipped with three-point engine suspension up to Chassis End No. 65 00172 and with four-point engine suspension as from Chassis End No. 65 00173.

B. Four-Point Engine Suspension on Models 190 SL, 220 S, and 220 SE as well as on Model 219 with Hydraulic Automatic Clutch

Rear rubber mountings

Model	Part No. of rubber mountings		Color code	Shore hardness of rubber
	left	right		
220 S, 220 SE, and 219 with hydraulic automatic clutch	121 223 00 12 optional 121 223 02 12	121 223 01 12 optional 121 223 03 12	green	70°
190, 190 SL 2 nd version	120 223 04 12 optional 120 223 06 12	120 223 05 12 optional 120 223 07 12	red	40°

On Models 220 S and 220 SE and on Model 219 with hydraulic automatic clutch the rear mountings are harder than the front mountings and are not interchangeable.

On Models 190 and 190 SL with four-point engine suspension the front and rear engine mountings are identical.